



CO-ORDINATION OF NOTIFIED BODIES
PPE Regulation 2016/425

PPE-R/01.006
Version 1

RECOMMENDATION FOR USE

Number of pages: 1	Approval stage :	Approved on :
Origin : Vertical Group 1	<input checked="" type="checkbox"/> Vertical Group	21.04.2018
	<input checked="" type="checkbox"/> Horizontal Committee	21.04.2018
	<input checked="" type="checkbox"/> EU PPE Expert Group	03.05.2021
Question related to <input type="checkbox"/> PPE Regulation	<input checked="" type="checkbox"/> EN/prEN: Various	<input type="checkbox"/> Other:
Article:	Annex:	Clause:
Key words: Kerbstone anvil		
Question: How shall a test be performed using the kerbstone anvil? <i>The following standards are affected:</i> EN 966 : 1996 (+A1/A2) & EN 966 : 2012 clause 7.2.3 EN 1077 : 2007 clause 5.5 (refers to EN 13087-2 : 2000 cl. 5.3) EN 1078 : 1997 (+A1) & EN 1078 : 2012 clause 5.4 EN 1080 : 1997 (+A1) & EN 1080 : 2013 clause 5.4 EN 13087-2 : 2000 (+A1) & EN 13087-2 : 2012 clause 5.3 EN 13781 : 2001 & EN 13781 : 2012 clause 5.4		
Solution: The kerbstone anvil simulates the pavement edge; this means it has to be considered of endless length. For practical and technical reasons these anvils have a limited length as specified in the standards. Test shall be performed in such a way that the edges of the anvil, as far as possible, do not affect the results (for example by directly contacting, during positioning, the headform).		