


|   |  |  |
|---|--|--|
|    | <b>CO-ORDINATION OF NOTIFIED BODIES</b><br><b>PPE Regulation 2016/425</b><br><br><b>RECOMMENDATION FOR USE</b>   | PPE-R/11.154<br>Version 01   |
| Number of pages: 1  | Approval stage : <span style="float: right;">Approved on :</span>  |  |
| Origin : Horizontal Committee   | <input checked="" type="checkbox"/> Vertical Group<br><input checked="" type="checkbox"/> Horizontal Committee<br><input type="checkbox"/> EU PPE Expert Group | <span style="float: right;">09/10/2024</span><br><span style="float: right;">20/03/2025</span> |
| Question related to <input type="checkbox"/> PPE Regulation <input type="checkbox"/> PPE Guidelines <input checked="" type="checkbox"/> EN/prEN: EN 360:2023 <input type="checkbox"/> Other:  |  |  |
| Article: <span style="margin-left: 100px;">Annex:</span> <span style="margin-left: 100px;">Clause:</span>   |  |  |
| Key words: Maximum rated load, application  |  |  |
| Question:<br>Can a Retractable Fall Arrestor EN 360:2023 claim different maximum rated loads on marking and on instructions and information for different applications?   |  |  |
| Solution:<br>Reference document: TC160/WG2/N867 from January 2024<br><br>In recognition that EN 360:2023 covers more than one application (e.g., vertical, horizontal, foot level,... with the same device), the maximum rated load shall be the same for all claimed applications. |  |  |