

	CO-ORDINATION OF NOTIFIED BODIES PPE Regulation 2016/425 RECOMMENDATION FOR USE	PPE-R/01.072 Version 01
Number of pages: 1	Approval stage : Approved on :	
Origin : Vertical Group 1	<input checked="" type="checkbox"/> Vertical Group 09/06/2021 <input checked="" type="checkbox"/> Horizontal Committee 30/04/2022 <input checked="" type="checkbox"/> EU PPE Expert Group 31/08/2023	
Question related to <input type="checkbox"/> PPE Regulation <input type="checkbox"/> PPE Guidelines <input checked="" type="checkbox"/> EN/prEN: EN443:2008 <input type="checkbox"/> Other:		
Article: Annex: Clause: 4.14 a)		
Key words: Horizontal field of vision		
Question: From which points should field of vision in the horizontal directions be assessed?		
Solution: The horizontal field of vision should be assessed from points L1 and L2 only. Rationale EN 443:2008 clause 4.14 specifies requirements for horizontal field of vision but does not state from where it should be measured. EN 443:2008 clause 5.16 states that testing shall be performed in accordance with EN 13087-6 (undated). EN 443:2008 includes figure 4 which appears to show the horizontal field of vision extending from point L and K. EN 13087-6:2012 clause 5.4 clearly states that horizontal field of vision is measured from points L1 and L2 so figure 4 of EN 443:2008 should be disregarded.		