

CO-ORDINATION OF NOTIFIED BODIES PPE Regulation 2016/425

PPE-R/11.098 Version 1

RECOMMENDATION FOR USE

Number of pages: 1	Approval stage :	Approved on :
Origin: Vertical Group 11 'Protection against Falls from a Height'	✓ Vertical Group✓ Horizontal Committee✓ EU PPE Working Group	21.04.2018 27.12.2018 29.11.2019
Question related to PPE Regulation PPE Guidelines	☑ EN/prEN: EN 795:2012	Other:
Article: Annex:	Clause:	
Key words:		
Anchor device, type B, lanyard		
Question:		
Is there any limitation of the length of anchor devices type B made of lanyard (textile, wire rope,)?		
and the drift in the length of		
Solution:		
No, at least because in some cases the distance between the structure and the user is important and cannot be reduced, there is no limitation of the length of anchor devices type B made of lanyard.		
But as these devices could be misused (e.g. climbing above the low attachment) they shall conform to following complementary requirements:		
1- Marking: the end attachment (or both ends if both can be used as tail) shall show a special warning to forbid to climb above the attachment (to avoid free fall) and to require to stay below the attachment (to avoid pendulum effect). Drawings can be used		
2- Instructions for use: shall include a warning about the risk of failure of the product in case of climbing above the attachment point and to require to stay below the attachment point.		